

# MANUAL FOR GRAPHIC OR BANNER PREPARATION

Roll Up

**RO**

Width [mm]: **600, 800, 850, 1000, 1200, 1500, 2000**

Height [mm]: **2000**

## PREPARATION OF GRAPHICS FOR PRODUCTION

### RASTER AND VECTOR DATA

- Prepare the graphics in the non-color PDF or TIFF format,
- output in CMYK color mode,
- image quality 100-300 dpi (Check the image quality by increasing the graphic to 100%. If the quality is OK you will need 100 dpi. But if the quality is worse you need to use better source data),
- size 1:1 according to dimensions for graphics preparation,
- convert fonts into curves or attach them to a file.

### EQUIPMENT AND MOUNT INSTALLATION

- Prepare the banner according to the attached templates,
- the width of the rollup graphic is the same as the width of the ordered rollup,
- in roll ups with telescopic rods is possible variable height (MAG, SPOT, CLEVER, ELITE, SNAP),
- we recommend inserting graphics into invisible installation parts (in case of change last-minute mechanics) - at the top 1 cm for insertion into the bar and at the bottom 10 cm for mechanics of rollup.

### BANNER SELECTION AND INSTALLATION

- We recommend printing on a polyester textile banner (PES) that perfectly holds the shape and do not twist; It is also suitable a polypropylene film (PP film) or a PVC banner up to 450 g / m<sup>2</sup>.

## DRAWING FOR PREPARING GRAPHICS

